

Pope Wiped-Film Still Canna Model Comparison



Pope Scientific's Wiped-Film Still equipment and technology trace back to 1976, and remain proudly built and supported in Wisconsin, USA. Over the years Pope has served many industries world-wide, including pharma, food, oils, specialty chemicals and many more. From the start of legalization, Pope's stills became and remain the standard and leader in extract distillation. We offer a wide range of still sizes to accommodate our customer's throughput requirements. In addition to the single-stage units listed below, fully automated, turnkey multistage systems are available.

	POPE 2" CANNASTILL	POPE 4" CANNASTILL	POPE 6" CANNASTILL	POPE PROPASS 600	POPE 9" CANNASTILL	POPE 12" CANNASTILL
Evaporator diameter	2"	4"	6"	6"	9"	12"
Material	Glass (SS available)	Glass (SS available)	Glass (SS available)	316L Stainless	316L Stainless	316L Stainless
Feed Rate	0.2 - 0.6 kg/hr with glass body and condenser	0.5 to 2 kg/hr with glass body and condenser	1-4 kg/hr with glass body and condenser	3 to 10 kg/hr	20-30 kg/hr	40-60 kg/hr
Evaporator surface area	0.033m ²	0.11m ²	0.22m ²	0.22 m ²	0.5m ²	1m ²
Ultimate vacuum (clean and dry)	0.008 to 0.02 Torr	0.008 to 0.02 Torr	0.008 to 0.02 Torr	0.008 to 0.02 Torr	0.008 to 0.02 Torr	0.008 to 0.02 Torr
Warranty	Limited 1 year warranty	Limited 1 year warranty	Limited 1 year warranty	Limited 2 year warranty	Limited 1 year warranty	Limited 1 year warranty
Dimensions	66"W x 22"D x 66"H	70"W x 60"D x 87"H	76"W x 60"D x 90"H	68"W x 51"D x 91"H	92"W x 60"D x 150"H	92"W x 88"D x 175"H
Electrical	60Hz Installations: 60 Amps @ 120V/1ph 50Hz Installations: 43 Amps @ 240V/1ph	60Hz Installations: 52 Amps @ 120V/1ph, plus 14 Amps @ 240V/1ph 50Hz Installations: 61 Amps @ 240V/1ph	60Hz Installations: 70 Amps @ 120V/1ph, plus 35 Amps @ 240V/1ph 50Hz Installations: 83 Amps @ 240V/1ph	208V, 3-phase (WYE), 75 FLA (Others available)	460V, 3-phase, 120 FLA (Others available)	460V, 3-phase, 150 FLA (Others available)